

PR7 Specification



| | |
|----------------------------|--|
| Size/Weight/Colour | |
| Size | 92mm*60mm*25mm(camera body) |
| Weight | 165g |
| Durability | |
| Shock Proof | 3m |
| Video/Picture/Audio | |
| Coding | H.264/H.265 |
| Wide Angle Lens | 140 degrees |
| Video Resolution | Can support 1440P30 but set at 1080P |
| Video Format | MP4 |
| Night Vision | Enhanced Low Light Capture |
| Storage | 64GB |
| Upload Speed | Up to 70MB |
| Secure AES Encryption | AES 256 |
| Bluetooth | Yes |
| ONVIF Protocol | Yes |
| Remote Cam Option | Yes |
| Upload Options | 6 |
| Pre-Record | |
| Pre-Record Time | 30 seconds, can be configured to customer requirements |
| Battery | |
| Recording Time | Up to 12 hours |

| | |
|--|--|
| Standby Time | 150 hours |
| Charging Time | 4 hours |
| Hardware Interface | |
| Pogo Pin connection | Support dock & go operation |
| Merge Solution | |
| Standard Mount | 360 degrees rotatable crocodile mount |
| Optional Mount | MOLLE compatible mount |
| Video Stamp | |
| Content Supported | User ID/Device ID/Date/Time/Geo-tage/Customise Strings |
| Indicators | |
| 3 Colour LED indicator for camera status | |
| 3 Colour LED indicator for battery level | |